

## E5CC/E5EC TEMPERATURE CONTROLLER

High performance with simplicity



- » Unique performance in temperature control
- » High-contrast display
- » Easy set-up and operation

# The new standard in temperature control...


*Omron has been an active innovator in temperature control since introducing its first temperature controller in 1967. Now temperature control has taken a giant leap forward with Omron's next generation of controllers – the E5CC/E5EC, which set new global standards in the crucial areas of precision, user friendliness and control performance. The E5CC/E5EC series will save you time and effort in set-up and operation, while enabling faster and more accurate monitoring/control of your process. The high-visibility display of the new series is also extremely easy to read and virtually eliminates any possibility for human error.*

## Key features

- High-contrast, white LCD display visible from large distances and from any angle
- Easy to set up, and operate intuitively via CX-Thermo without power supply
- 50 ms sampling period for fast and precise regulation
- Functions for diagnosis for secure operations (see note 1)

**NEW GENERATION**





## ...is higher in every respect

### Clearer LCD display

The large, high-contrast, white LCD display contributes to the exceptional clarity and therefore readability of the E5CC/E5EC series. The display can be read unambiguously from greater distances and from much wider viewing angles than normal.

### Easy set-up and operation

Coupled with the autotuning algorithms, which greatly reduce set-up and commissioning time, Omron's CX-Thermo support software has been specially developed for use with the E5CC/E5EC series. This enables faster parameter set-up, easier device adjustment and simpler maintenance.

### Unique performance

Although intrinsic high sampling speed and high precision are built into the E5CC/E5EC series, Omron's 2-PID control is a key factor behind the advantage it offers over standard controllers. Using a powerful algorithm, it makes all the difference to control stability and thus the quality of your products.

## High-contrast display

White LCD offers the greatest contrast to the black instrumentation backgrounds found in panels and the lighting conditions found in most control rooms. Despite the compact dimensions of the E5CC/E5EC series, the use of white LCD technology means that the 15-18 mm display height gives maximum clarity for its size. The distance and viewing angle of the high-contrast, white LCD light display is also far less critical for viewers, ensuring correct readings every time.



The white LCD display is easy to read in the subdued lighting conditions found in most control rooms.



The display remains easy to read even from wide viewing angles.



## Save space!

The compact and space-saving design of the new E5CC/E5EC controller generation requires less panel depth (60 mm), allowing quick snap-mounting and easy installation even under very cramped conditions.

Thanks to the IP66 protection of the front cover, the E5CC/E5EC can withstand humid environments and also be cleaned with non-aggressive fluids.

## Easy to connect, set-up and operate

The E5CC/E5EC series is extremely easy to connect, set-up and operate in just a few simple steps using the instrument's five front keys. Omron's CX-Thermo software and new navigation assistant for intuitive settings offers the fastest possible parameter setting, easier device adjustment and simpler maintenance.

### Ready to operate in only three steps:

**1** Connect – no extra wiring necessary\*



**2** Navigate and set-up



**3** Operate



\* CX-Thermo V4.4 must be preinstalled. It is available as a bundle together with USB converter E58-CIFQ2 and E58-CIFQ2-E

## Time-saving 'shift key' for changing the set value

Key assignment can be changed for RUN/STOP or AT execution/STOP according to the user's setting!



## Unique performance with simplicity...

### ...and more control functionality


With key features like simplicity in operation, Omron's patented PID control, 50ms sampling period and the ability to handle multi-functional input and output types, the E5CC/E5EC sets a new standard in fast and precise temperature regulation. It has all the familiar functionality available from existing Omron temperature controllers to cover virtually any general-purpose demand. And naturally, the versatile E5CC/E5EC series is available with input/output combinations to perfectly match all of your requirements.

#### Extended inputs & outputs

- Remote SP input
- Transfer output (voltage 1-5 V output) added
- Event input
- Auxiliary output

#### New functions

- Timer function
- Heat & Cool PID function
- SP ramp function
- Enhanced alarm mode
- Enhanced manual output





## Global availability, support and network

### Providing you with the support you need to operate globally

Whether you want to take your existing products into new industrial sectors, or whether you want to expand your business into entirely new geographical markets, Omron can help. We aim to offer the same level of support globally, without forgetting local needs.

We have production facilities on every continent.

Our smart communications network and seamless global support means we can provide you with parts and technical support wherever you sell your machines. And all of our components comply with major international standards, to ensure problem-free integration. It's all there for you.

#### Facts and figures

- Over 35,000 employees
- Almost 200 locations
- Presence in every continent
- Knowledge-sharing through our global infrastructure
- Local R&D facilities synchronised to local needs
- Local factories to ensure quick response
- Global pricing terms
- Global support

## E5CC model list (all models 3 auxiliary outputs)

Output	Option No.*	Order code AC110-240V	Order code AC/DC24V
<b>Out 1:</b> Relay <b>Out 2:</b> non		E5CC-RX3A5M-000	E5CC-RX3D5M-000
	001	E5CC-RX3A5M-001	E5CC-RX3D5M-001
	003	E5CC-RX3A5M-003	E5CC-RX3D5M-003
	005	E5CC-RX3A5M-005	E5CC-RX3D5M-005
	006	E5CC-RX3A5M-006	E5CC-RX3D5M-006
	007	E5CC-RX3A5M-007	E5CC-RX3D5M-007
	<b>Out 1:</b> Voltage (pulse) <b>Out 2:</b> non		E5CC-QX3A5M-000
001		E5CC-QX3A5M-001	E5CC-QX3D5M-001
003		E5CC-QX3A5M-003	E5CC-QX3D5M-003
005		E5CC-QX3A5M-005	E5CC-QX3D5M-005
006		E5CC-QX3A5M-006	E5CC-QX3D5M-006
007		E5CC-QX3A5M-007	E5CC-QX3D5M-007
<b>Out 1:</b> Voltage (pulse) <b>Out 2:</b> Voltage (pulse)			E5CC-QQ3A5M-000
	001	E5CC-QQ3A5M-001	E5CC-QQ3D5M-001
	003	E5CC-QQ3A5M-003	E5CC-QQ3D5M-003
	005	E5CC-QQ3A5M-005	E5CC-QQ3D5M-005
	006	E5CC-QQ3A5M-006	E5CC-QQ3D5M-006
	007	E5CC-QQ3A5M-007	E5CC-QQ3D5M-007
	<b>Out 1:</b> Linear current <b>Out 2:</b> non		E5CC-CX3A5M-000
004		E5CC-CX3A5M-004	E5CC-CX3D5M-004
005		E5CC-CX3A5M-005	E5CC-CX3D5M-005
006		E5CC-CX3A5M-006	E5CC-CX3D5M-006
007		E5CC-CX3A5M-007	E5CC-CX3D5M-007

As well as these models other models are available on request. Please contact the local sales office for special requests.

### \* Option No.:

**001**

Event Input 2,  
Heater Burnout SSR  
defect detection

**003**

Communication  
3-phase heater  
alarm

**004**

Event Input 2,  
Communication

**005**

Event Input 4

**006**

Event Input 2,  
Transfer output



## E5EC model list (all models 4 auxiliary outputs)

Output	Option No.*	Order code AC110-240V	Order code AC/DC24V
Out 1: Relay Out 2: non		E5EC-RX4A5M-000	E5EC-RX4D5M-000
	009	E5EC-RX4A5M-009	E5EC-RX4D5M-009
	010	E5EC-RX4A5M-010	E5EC-RX4D5M-010
	011	E5EC-RX4A5M-011	E5EC-RX4D5M-011
Out 1: Relay Out 2: Relay		E5EC-RR4A5M-000	E5EC-RR4D5M-000
	009	E5EC-RR4A5M-009	E5EC-RR4D5M-009
	010	E5EC-RR4A5M-010	E5EC-RR4D5M-010
	011	E5EC-RR4A5M-011	E5EC-RR4A5M-011
Out 1: Voltage (pulse) Out 2: non		E5EC-QX4A5M-000	E5EC-QX4D5M-000
	009	E5EC-QX4A5M-009	E5EC-QX4D5M-009
	010	E5EC-QX4A5M-010	E5EC-QX4D5M-010
	011	E5EC-QX4A5M-011	E5EC-QX4D5M-011
Out 1: Voltage (pulse) Out 2: Voltage (pulse)		E5EC-QQ4A5M-000	E5EC-QQ4D5M-000
	009	E5EC-QQ4A5M-009	E5EC-QQ4D5M-009
	010	E5EC-QQ4A5M-010	E5EC-QQ4D5M-010
	011	E5EC-QQ4A5M-011	E5EC-QQ4D5M-011
Out 1: Voltage (pulse) Out 2: Relay		E5EC-QR4A5M-000	E5EC-QR4D5M-000
	009	E5EC-QR4A5M-009	E5EC-QR4D5M-009
	010	E5EC-QR4A5M-010	E5EC-QR4D5M-010
	011	E5EC-QR4A5M-011	E5EC-QR4D5M-011
Out 1: Linear current Out 2: non		E5EC-CX4A5M-000	E5EC-CX4D5M-000
	004	E5EC-CX4A5M-004	E5EC-CX4D5M-004
	005	E5EC-CX4A5M-005	E5EC-CX4D5M-005
	013	E5EC-CX4A5M-013	E5EC-CX4D5M-013
	014	E5EC-CX4A5M-014	E5EC-CX4D5M-014
Out 1: Linear current Out 2: Linear current		E5EC-CC4A5M-000	E5EC-CC4D5M-000
	004	E5EC-CC4A5M-004	E5EC-CC4D5M-004
	005	E5EC-CC4A5M-005	E5EC-CC4D5M-005
	013	E5EC-CC4A5M-013	E5EC-CC4D5M-013
	014	E5EC-CC4A5M-014	E5EC-CC4D5M-014

### 007

Event Input 2,  
Remote SP

### 009

Event Input 2,  
Communication  
3-phase heater  
alarm

### 010

Event Input 4  
Heater Burnout SSR  
defect detection

### 011

Event Input 6,  
Remote SP Heater  
Burnout SSR defect  
detection, Transfer  
output

### 013

Event Input 6,  
Remote SP, Transfer  
output

### 014

Event Input 4,  
Communication  
Remote SP, Transfer  
output



### High performance & simplicity

The next generation E5\_C temperature controller is setting a new global standard in terms of precision and user-friendly design. Best control performance, easy set-up and outstanding visibility of the white IP66 LCD display have been integrated into a space-saving housing with only 60 mm of depth.


- Fast and precise regulation: 50 ms sampling loop period time
- Easy to set up, and operate intuitively via CX-Thermo without power supply
- Best contrast display using white LCD technology which is visible from a far distance and from any angle
- Useful alarm and diagnosis functions for secure operation

### Specifications

	E5CC	E5EC
<b>Power supply voltage</b>	A in model number: 100 to 240 VAC, 50/60 Hz D in model number: 24 VAC, 50/60 Hz; 24 VDC	
<b>Operating voltage range</b>	85% to 110% of rated supply voltage	
<b>Power consumption</b>	100 to 240 VAC: 4.5 VA (max.) 24 VAC/VDC: 2.5 VA/2 W (max.)	
<b>Sensor input</b>	– Temperature inputs Thermocouple: K, J, T, E, L, U, N, R, S, B, W, or PL II Platinum resistance thermometer: Pt100 or JPt100 Infrared temperature sensor: 10 to 70°C, 60 to 120°C, 115 to 165°C, or 140 to 260°C  – Analog inputs Current input (mA): 4 to 20, 0 to 20 Voltage input (V): 1 to 5, 0 to 5, 0 to 10	
<b>Input impedance</b>	Current input: 150 Ω max., Voltage input: 1 MΩ min. (Use a 1:1 connection when connecting the ES2-HB.)	
<b>Control method</b>	ON/OFF control or 2-PID control (with auto-tuning)	
<b>Indication accuracy</b>	Thermocouple input: ±0.3% of indicated value Platinum resistance thermometer input: ±0.2% of indicated value Analog input: ±0.2% FS ±1 digit max.	
<b>Auto-Tuning</b>	Yes, 40%/100% MV output limit selection. When using Heat/Cool: Automatic cool gain adjustment	
<b>Self-Tuning</b>	Yes	
<b>Control outputs 1</b>	<b>Relay output</b>	SPST-NO, 250 VAC, 3 A (resistive load), electrical life: 100,000 operations, minimum applicable load: 5 V, 10 mA
	<b>Voltage output (for driving SSR)</b>	Output voltage: 12 VDC ±20% (PNP), max. load current: 21 mA, with short-circuit protection circuit
	<b>Current output</b>	4 to 20 mA DC/0 to 20 mA DC, load: 500 Ω max., resolution: approx. 10,000
<b>Control outputs 2</b>	<b>Voltage output (for driving SSR)</b>	Output voltage: 12 VDC ±20% (PNP), max. load current: 21 mA, with short-circuit protection circuit
<b>Auxiliary outputs</b>	<b>Number of outputs</b>	0 or 2 or 3 or 4 max (depends on the model)
	<b>Output specifications</b>	Relay output: SPST-NO, 250 VAC, 3 A (resistive load), electrical life: 100,000 operations, minimum applicable load: 5 V, 10 mA
<b>Event inputs</b>	<b>Number of inputs</b>	6 max
	<b>External contact input specifications</b>	Contact input: ON: 1 kΩ max., OFF: 100 kΩ min. Non-contact input: ON: Residual voltage: 1.5 V max., OFF: Leakage current: 0.1 mA max. Current flow: Approx. 7 mA per contact
<b>Setting method</b>	Digital setting using front panel keys or via Remote Software CX-Thermo V4.4	
<b>Indication method</b>	11-segment digital display and individual indicators	
<b>Multi SP</b>	Up to eight set points (SP0 to SP7) can be saved and selected using event inputs, key operations, or serial communications.	
<b>Other functions</b>	Manual output, heating/cooling control, loop burnout alarm, SP ramp, other alarm functions, heater burnout detection (including SSR failure detection), 40% AT, 100% AT, MV limiter, input digital filter, self-tuning, temperature input shift, run/stop, protection functions, extraction of square root, MV change rate limit, logic operations, PV/SV status display, simple program, automatic cooling coefficient adjustment	
<b>Ambient operating temperature</b>	-10 to 55°C (with no condensation or icing)	
<b>Ambient operating humidity</b>	25% to 85%	
<b>Storage temperature</b>	-25 to 65°C (with no condensation or icing)	
<b>QLP (Quick Link Port – USB connection via PC)</b>	Yes	
<b>Degree of protection</b>	Front panel: IP66	
<b>Sampling period</b>	50 ms	
<b>Size in mm (HxWxD)</b>	48x48x64	48x96x64

## USB communication cable E58-CIFQ2

	E5CC	E5EC
E58-CIFQ2	■	■
E58-CIFQ2-E	-	■



## E5CC/E5EC optional tools

Option	Order code
USB based configuration cable	E58-CIFQ2, E58-CIFQ2-E (for E5EC)
PC based configuration and tuning software	EST2-2C-MV4

OMRON EUROPE B.V. Wegalaan 67-69, NL-2132 JD, Hoofddorp, The Netherlands. Tel: +31 (0) 23 568 13 00 Fax: +31 (0) 23 568 13 88 [www.industrial.omron.eu](http://www.industrial.omron.eu)

**Austria**

Tel: +43 (0) 2236 377 800  
[www.industrial.omron.at](http://www.industrial.omron.at)

**Belgium**

Tel: +32 (0) 2 466 24 80  
[www.industrial.omron.be](http://www.industrial.omron.be)

**Czech Republic**

Tel: +420 234 602 602  
[www.industrial.omron.cz](http://www.industrial.omron.cz)

**Denmark**

Tel: +45 43 44 00 11  
[www.industrial.omron.dk](http://www.industrial.omron.dk)

**Finland**

Tel: +358 (0) 207 464 200  
[www.industrial.omron.fi](http://www.industrial.omron.fi)

**France**

Tel: +33 (0) 1 56 63 70 00  
[www.industrial.omron.fr](http://www.industrial.omron.fr)

**Germany**

Tel: +49 (0) 2173 680 00  
[www.industrial.omron.de](http://www.industrial.omron.de)

**Hungary**

Tel: +36 1 399 30 50  
[www.industrial.omron.hu](http://www.industrial.omron.hu)

**Italy**

Tel: +39 02 326 81  
[www.industrial.omron.it](http://www.industrial.omron.it)

**Netherlands**

Tel: +31 (0) 23 568 11 00  
[www.industrial.omron.nl](http://www.industrial.omron.nl)

**Norway**

Tel: +47 (0) 22 65 75 00  
[www.industrial.omron.no](http://www.industrial.omron.no)

**Poland**

Tel: +48 (0) 22 645 78 60  
[www.industrial.omron.pl](http://www.industrial.omron.pl)

**Portugal**

Tel: +351 21 942 94 00  
[www.industrial.omron.pt](http://www.industrial.omron.pt)

**Russia**

Tel: +7 495 648 94 50  
[www.industrial.omron.ru](http://www.industrial.omron.ru)

**South Africa**

Tel: +27 (0)11 579 2600  
[www.industrial.omron.co.za](http://www.industrial.omron.co.za)

**Spain**

Tel: +34 913 777 900  
[www.industrial.omron.es](http://www.industrial.omron.es)

**Sweden**

Tel: +46 (0) 8 632 35 00  
[www.industrial.omron.se](http://www.industrial.omron.se)

**Switzerland**

Tel: +41 (0) 41 748 13 13  
[www.industrial.omron.ch](http://www.industrial.omron.ch)

**Turkey**

Tel: +90 212 467 30 00  
[www.industrial.omron.com.tr](http://www.industrial.omron.com.tr)

**United Kingdom**

Tel: +44 (0) 870 752 08 61  
[www.industrial.omron.co.uk](http://www.industrial.omron.co.uk)

**More Omron representatives**  
[www.industrial.omron.eu](http://www.industrial.omron.eu)

CD\_EN-01+E5\_C+Brochure+EU

**Automation Systems**

- Programmable logic controllers (PLC) • Human machine interfaces (HMI) • Remote I/O
- Industrial PC's • Software

**Motion & Drives**

- Motion controllers • Servo systems • Inverters • Robots

**Control Components**

- Temperature controllers • Power supplies • Timers • Counters • Programmable relays
- Digital panel indicators • Electromechanical relays • Monitoring products • Solid-state relays
- Limit switches • Pushbutton switches • Low voltage switch gear

**Sensing & Safety**

- Photoelectric sensors • Inductive sensors • Capacitive & pressure sensors
- Cable connectors • Displacement & width-measuring sensors • Vision systems
- Safety networks • Safety sensors • Safety units/relay units • Safety door/guard lock switches