

XG series

SCARA robots


SCARA robots for industrial applications:

- Higher reliability (no belts in XG series, no electronic parts in movement). *1
- Higher precision and speed.
- Minimum maintenance.
- Easier to use.
- Higher rigidity.
- Very compact design.



*1: This series is also available as wall-hanging type. For further information, please ask your OMRON representative.

System configuration



YRC Robot controller

Specifications

Item	Description			
YRC	YRC robot controller			
Basic specifications	Number of controllable axes			
	4 axes maximum (Control simultaneously: 4 axes)			
	Controllable robots			
	SCARA robots			
	Maximum power consumption			
	2500 VA			
Capacity of the connected motor				
1600 W				
Dimensions (WxHxD)				
180x250x235 mm				
Weight				
6.5 kg				
Input power supply	Control power supply	Single phase AC200 to 230 V +/-10% maximum (50/60 Hz)		
	Motor power supply	Single phase AC200 to 230 V +/-10% maximum (50/60 Hz)		
Axis control	Drive method			
	AC full-digital software servo			
	Position detection method			
	Multi-turn resolver with data backup function, Magnetic linear scale			
	Operating method			
	PTP (Point to point), Linear interpolation, Circular interpolation, ARCH			
	Coordinate system			
	Joint coordinates, Cartesian coordinates			
	Position indication units			
Pulses, mm (millimeters), deg (degrees)				
Speed setting				
1% to 100% (In units of 1%. However speed is in units of 0.01% during single-axis operation by DRIVE statement)				
Acceleration setting				
1. Automatic acceleration setting based on robot model type and end mass parameter 2. Setting based on acceleration and deceleration parameter (Setting by 1% unit)				
Resolution				
16384 P/rev, 1 micron				
Origin search method				
Incremental, absolute, semi-absolute				
Program	Program language			
	PSEUDO-BASIC (Conforming to JIS B8439 SLIM Language)			
	Multitasks			
	8 tasks maximum			
Sequence program				
1 program				
Point-data input method				
Manual data input (coordinate value input), Direct teaching, Teaching playback				
Memory	Memory capacity			
	364 KB (total capacity of program and points) (available program capacity during use of maximum number of points is 84 KB)			
	Programs			
	100 program (Max.) 9.999: maximum lines per program 98 KB: maximum capacity per program			
	Points			
10.000 points: maximum number of points				
Memory Backup battery				
Lithium metallic battery (service life 4 years at a 0°C to 40°C)				
Internal flash memory				
512 KB (ALL data only)				
External input/output	STD.DIO	I/O input	General input 16 points, dedicated input 10 points (NPN/PNP specifications selectable)	
		I/O output	General output 8 points, dedicated output 11 points	
	SAFETY		Emergency stop input (Relay contact), Service mode input (NPN/PNP specification is set according to STD.DIO setting)	
	Brake output		Relay contact	
	Origin sensor input		Connectable to DC 24 V normally-closed contact sensor	
	External communications		RS232C: 1CH D-SUB9 (female) RS422: 1CH (Dedicated PB)	
	Options	Slots		4
		Type		Optional input/output (NPN/PNP): General input 24 points / General output 16 points
				CC-Link: Dedicated input 16 points, Dedicated output 16 points, General input 96 points, General output 96 points (4 nodes occupied)
				DeviceNet: Dedicated input 16 points, Dedicated output 16 points, General input 96 points, General output 96 points
				Profibus: Dedicated input 16 points, Dedicated output 16 points, General input 96 points, General output 96 points
				Ethernet: IEEE802.3 10Mbps (10BASE-T)
				IVY: Camera input (2ch), camera trigger input, PC connection input
		Tracking: AB phase input, lighting trigger input, lighting power supply input/output		
		Lighting control: lighting trigger input, lighting power supply input/output		
Options	Programming box		PB (with enable switch)	
	Support software for PC		SCARA STUDIO	
General specifications	Operating temperature		0°C to 40°C	
	Storage temperature		-10°C to 65°C	
	Operating humidity		35% to 85% RH (non-condensing)	
	Absolute backup battery		Lithium metallic battery 3.6 V 5400 mAh (2700 mAh x 2)	
	Absolute data backup period		1 year (in state with no power applied)	
	Noise immunity		IEC61000-4-4 Level 3	
	Protective structure		IP10	

YRC-Optional Input/Output unit (PNP/NPN)

Item	Description
R6YACMA241 (NPN) R6YACMA242 (PNP)	Optional Input/Output unit
Optional Input/Output (NPN/PNP)	24 General purpose input, 16 General purpose output

YRC-DeviceNet slave unit

Item	Description	
R6YACDRT01	DeviceNet slave unit	
Applicable controllers	YRC	
Applicable DeviceNet specifications	Volume 1 Release 2.0 / Volume 2 Release 2.0	
Device Profile Name	Generic Device (device number 0)	
Number of occupied CH ^{*1}	Normal: Input/Output 24ch each, Compact: Input/Output 2ch each	
MAC ID setting	0 to 63	
Transmission speed setting	500 Kbps, 250 Kbps, 125 Kbps (set using DIP switch on board)	
DeviceNet I/O ²	Normal	General input 96 points, General output 96 points, Dedicated input 16 points, Dedicated output 16 points
	Compact	General input 16 points, General output 16 points, Dedicated input 16 points, Dedicated output 16 points
Parallel external I/O	The master module and up to four ports can be controlled regardless of the robot program by using the pseudoserialization function	
Network length	Overall length ^{*3}	100 m/500 Kbps, 250 m/250 Kbps, 500 m/125 Kbps
	Branch length / Overall branch length	6 m max./39 m max., 6 m max./78 m max., 6 m max./156 m max.
Monitor LED	MS (Module Status), NS (Network Status)	

*1 Use the robot parameter to select Normal or Compact.

*2 Controller I/O are updated every 10ms.

*3 These values apply when a thick cable is used. The distance is less when a fine cable is used or when thick and fine cables are mixed in use.

YRC-Profibus slave unit

Item	Description
R6YACPRT01	Profibus slave unit
Applicable controllers	YRC
Communication profile	Profibus-DP slave
Number of occupied nodes	1 node
Setting of station address	1 to 99 (set using Rotary switch on board)
Setting of communication speed	9.6 Kbps, 19.2 Kbps, 93.75 Kbps, 187.5 Kbps, 500 Kbps, 1.5 Mbps, 3 Mbps, 6 Mbps, 12 Mbps (automatic recognition)
Profibus I/O ^{*1}	General input 96 points, General output 96 points, Dedicated input 16 points, Dedicated output 16 points
Parallel external I/O	The master module and up to four ports can be controlled regardless of the robot program by using the pseudoserialization function
Overall length	100 m/3 M-6 M-12 Mbps, 200 m/1.5 Mbps, 400 m/500 Kbps, 1000 m/187.5 Kbps, 1200 m/9.6 K- 19.2 K-93.75 Kbps
Monitor LED	RUN, ERR, SD, RD, DATA-EX

*1 The shortest I/O update interval of the controller is 10 ms but the actual I/O update time varies depending on the update time with the master station.

YRC-Ethernet unit

Item	Description
R6YACETN01	Ethernet unit
Applicable controllers	YRC
Network specification	As specified for Ethernet (IEEE802.3)
Connector specification	RJ-45 connector (8-pole modular connector) 1 port
Baud rate	10 Mbps (10BASE-T)
Communication mode	Half Duplex (Half-duplex)
Network protocol	Application layer: TELNET / Transport layer: TCP / IP Network layer: IP, ICMP, ARP / Data link layer: CSMA / CD Physical layer: 10BASE-T
Number of simultaneous log inputs	1
Setting of IP address, etc.	Set from PB
Monitor LED	Run, Collision, Link, Transmit, Receive

YRC-VISION board basic specifications

Item	Description	
R6YACVI01	VISION board	
Basic specifications	Applicable controller	YRC
	Pixels	640 (H) x 480 (V) (300,000 pixels, VGA)
	Settable part types	40 part types
	Connectable cameras	Maximum 2 units ^{*1}
	Camera types	Double speed compatible analog camera
	Memory	128 MB SDRAM, 256 MB miniSD card
	External I/F	Ethernet (100BASE-TX)
Search method	Edge search (Correlative edge filter, Sobel filter)	
Image input	Trigger	S/W trigger, H/W trigger, Camera internal synch
	External trigger input	2 points
Functions	Search function	Position offset, Auto registry of point data
Setup support functions	Calibration, image storage function ^{*2} (all images / specified image)	

*1 If connecting 2 units, then must be the same model.

*2 Requires Windows PC.

Accessories for YRC-VISION board

Item	Description
R6YACS1	CCD CAMERA
R6YACCV003	Camera cable 3.5 m
R6YACCV006	Camera cable 6 m
R6YACCV009	Camera cable 9.5 m (3.5 m + 6 m)
R6YACLE008	Lens 8 mm
R6YACLE012	Lens 12 mm
R6YACLE016	Lens 16 mm
R6YACLE025	Lens 25 mm
R6YACLR005	Close up ring 0.5 mm
R6YACLR010	Close up ring 1.0 mm
R6YACLR020	Close up ring 2.0 mm
R6YACLR050	Close up ring 5.0 mm

YRC-Tracking board basic specifications

Item	Description		
R6YACTR01	Tracking board		
Basic specifications	Lighting control section	Applicable controller	YRC
		Number of lighting connected units	Up to 2 units
		Light adjusting system	PWM control (0 to 100%) (Cycle 60 KHz) Stroboscopic light (10 to 33000 μs)
		Trigger	S/W trigger, H/W trigger
		External trigger input	2 points
		Lighting power input	12 VDC or 24 VDC (Supplied from outside commonly to 2 channels)
		Lighting output	When DC 12 V is supplied: Less than 30 W with 2 channels totaled When DC 24 V is supplied: Less than 60 W with 2 channels totaled
	Pulse input section	Number of encoder connected units	Up to 2 units
		Encoder power source	DC 5 V (Less than 500 mA with 2 channels totaled) (Supplied from controller)
		Applicable encoder	Line driver equivalent to 26LS31 / 26C31 (Conforming to RS422)
		Input phase	A, \bar{A} , B, \bar{B} , Z, \bar{Z}
		Maximum response frequency	2 MHz
		Counter / Step-up multiplication	0 to 65535 / Double, quadruple
		Other	Provided with broken wire detect function

Note: The tracking board is required when using the tracking function.

Accessories for YRC-Tracking board

Item	Description
R6YACCR005	Encoder cable for tracking 10m

YRC-Lighting control board basic specifications

Item	Description	
R6YACLI01	Lighting control board	
Basic specifications	Applicable controller	YRC
	Number of lighting connected units	Up to 2 units
	Light adjusting system	PWM control (0 to 100%) (Cycle 60KHz) Stroboscopic light (10 to 33000us)
	Trigger	S/W trigger, H/W trigger
	External trigger input	2 points
	Lighting power input	12VDC or 24VDC (Supplied from outside commonly to 2 channels)
	Lighting output	When DC12V is supplied: Less than 30W with 2 channels totaled When DC24V is supplied: Less than 60W with 2 channels totaled

Accessories for YRC-PB (Programming box)


Item	Description
R6YACPB005E	Programming box cable 5m
R6YACPB012E	Programming box cable 12m

Accessories for YRC-SCARA studio software

Item	Description
R6YACSSC1	Support software SCARA studio
R6YACCC005	Communication cable 9-9 pin

YRC-Nomenclature

Connector names




	Connector name	Function
①	XM/YM/ZM/RM	Connectors for servomotor drive
②	ROB I/O [XY/ZR]	Connectors for servomotor feedback and sensor signals
③	SAFETY	Input/output connector for safety function such as emergency stop
④	PB	Connector for PB
⑤	COM	RS-232C interface connector.
⑥	STD.DIO	Connector for dedicated input/output and standard generalpurpose input/output
⑦	OP.1 ,2, 3, 4	Connectors attached to optional expansion I/O boards
⑧	BATT [XY/ZR]	Battery connector for absolute backup
⑨	PB SEL	PB selector switch contact
⑩	RGEN [P/±/N]	Connector for regenerative unit
⑪	AC IN [L/N/L1/N1]	Terminal block for power cable. Use ring-tongue terminals to make connections.
⑫	FG	Ground terminal (±) . Provide Class D grounding (100 ohms or less) .


Dimensions

Standard YRC


Top view




Front view




Side view



Rear view




Bottom view




Note 1: When installing this controller using the supplied L-type brackets, remove the rubber feet on the bottom plate.

YRC with RGU2 option installed


Top view




Front view




Side view



Rear view




Bottom view




YRC with RGU3 option installed


Top view




Front view




Side view



Rear view



Bottom view



R6YXG120 TINY SERIES

Specifications

	X axis	Y axis	Z axis	R axis
Reach (mm)	120			
Maximum payload (kg)	1			
Repeatability ¹ (XYZ:mm) (R:°)	+/-0.005		+/-0.01	+/-0.004
Axis specifications	Arm length (mm)	45	75	50
	Rotation range (°)	+/-125	+/-145	----
Deceleration mechanism	Speed reducer	Harmonic drive	Harmonic drive	Ball screw
	Transmission method	Motor to speed reducer	Direct-coupled	
		Speed reducer to output	Direct-coupled	
AC servo motor output (W)	30	30	30	30
Maximum speed (XYZ:m/sec) (R:°/sec)	3.3		0.9	1700
Standard cycle time: with 0.1kg payload ² (sec)	0.33			
R axis allowable moment inertia ³ (kgm ²)	0.01			
User wiring (sq x pcs)	0.1 x 8			
User tubing (Outer diameter)	Ø4 x 2			
Movement limit setting	1.Soft limit 2.Mechanical stopper (X, Y, Z axis)			
Robot cable length (m)	Standard: 2 Option: 3.5, 5, 10			
Weight (kg) (Robot cable not included) ⁴	3.9			
Robot cable weight	0.9kg (2m) 1.5kg (3.5m) 2.1kg (5m) 4.2kg (10m)			

- *1 This is the value at a constant ambient temperature. (X,Y axes)
- *2 When moving 25mm in vertical direction and 100mm in horizontal direction reciprocally.
- *3 There are limits to the setting of the acceleration coefficient.
- *4 The overall weight of the robot is the total of the robot itself and the robot cable.


Controller

Controller	Power consumption (VA)	Operating method
YRC	300	Programming / I/O point trace / Remote command / Operation using RS-232C communication

Ordering information

Description	Model
SCARA Reach: 120mm, Vertical Stroke: 50mm, Max. payload: 1kg.	R6YXG12050YRC

Dimensions



R6YXG220 TINY SERIES

Specifications

		X axis	Y axis	Z axis	R axis
Reach (mm)		220			
Maximum payload (kg)		1			
Repeatability ¹ (XYZ:mm) (R:°)		+/-0.01			
Axis specifications	Arm length (mm)	111	109	100	----
	Rotation range (°)	+/-120	+/-140	----	+/-360
Deceleration mechanism	Speed reducer	Harmonic drive	Harmonic drive	Ball screw	Harmonic drive
	Transmission method	Motor to speed reducer	Direct-coupled		
		Speed reducer to output	Direct-coupled		
AC servo motor output (W)		50	30	30	30
Maximum speed (XYZ:m/sec) (R:°/sec)		3.4		0.7	1700
Standard cycle time: with 0.1kg payload ² (sec)		0.42			
R axis allowable moment inertia ³ (kgm ²)		0.01			
User wiring (sq x pcs)		0.1 x 6			
User tubing (Outer diameter)		Ø3 x 2			
Movement limit setting		1.Soft limit 2.Mechanical stopper (X, Y, Z axis)			
Robot cable length (m)		Standard: 3.5 Option: 5, 10			
Weight (kg) (Robot cable not included) ⁴		5.5			
Robot cable weight		1.5kg (3.5m) 2.1kg (5m) 4.2kg (10m)			

- *1 This is the value at a constant ambient temperature. (X, Y axes)
- *2 When moving 25mm in vertical direction and 100mm in horizontal direction reciprocally.
- *3 There are limits to the setting of the acceleration coefficient.
- *4 The overall weight of the robot is the total of the robot itself and the robot cable.


Controller

Controller	Power consumption (VA)	Operating method
YRC	500	Programming / I/O point trace / Remote command / Operation using RS-232C communication

Ordering information

Description	Model
SCARA Reach: 220mm, Vertical Stroke: 100mm, Max. payload: 1kg.	R6YXG220100YRC

Dimensions



R6YXGH600 XG SERIES

Specifications

		X axis	Y axis	Z axis	R axis
Reach (mm)		600			
Maximum payload (kg)		20			
Repeatability ^{*1} (XYZ:mm) (R:°)		+/-0.02		+/-0.01	+/-0.004
Axis specifications	Arm length (mm)	200	400	200	400
	Rotation range (°)	+/-130	+/-150	----	+/-360
Deceleration mechanism	Speed reducer	Harmonic drive	Harmonic drive	Ball screw	Harmonic drive
	Transmission method	Motor to speed reducer	Direct-coupled		
		Speed reducer to output	Direct-coupled		
AC servo motor output (W)		750	400	400	200
Maximum speed (XYZ:m/sec) (R:°/sec)		7.7		2.3	1.7
Standard cycle time: with 2kg payload ^{*2} (sec)		0.47			
R axis allowable moment inertia ^{*3} (kgm ²)		1			
User wiring (sq x pcs)		0.2 x 20			
User tubing (Outer diameter)		Ø6 x 3			
Movement limit setting		1.Soft limit 2.Mechanical stopper (X, Y, Z axis)			
Robot cable length (m)		Standard: 3.5 Option: 5, 10			
Weight (kg) (Excluding robot cable)		Z axis 200mm: 48, Z axis 400mm: 50			

- *1 This is the value at a constant ambient temperature. (X,Y axes)
- *2 When moving 25mm in vertical direction and 300mm in horizontal direction reciprocally.
- *3 There are limits to the setting of the acceleration coefficient.


Controller

Controller	Power consumption (VA)	Operating method
YRC	2500	Programming / I/O point trace / Remote command / Operation using RS-232C communication

Ordering information

Description	Model
SCARA Reach: 600mm, Vertical Stroke: 200mm, Max. payload: 20kg.	R6YXGH600200YRC
SCARA Reach: 600mm, Vertical Stroke: 400mm, Max. payload: 20kg.	R6YXGH600400YRC

Dimensions



R6YXG700 XG SERIES

Specifications

		X axis	Y axis	Z axis	R axis
Reach (mm)		700			
Maximum payload (kg)		20			
Repeatability ¹ (XYZ:mm) (R:°)		+/-0.02		+/-0.01	+/-0.004
Axis specifications	Arm length (mm)	300	400	200	400
	Rotation range (°)	+/-130	+/-150	----	+/-360
Deceleration mechanism	Speed reducer	Harmonic drive	Harmonic drive	Ball screw	Harmonic drive
	Transmission method	Motor to speed reducer	Direct-coupled		
		Speed reducer to output	Direct-coupled		
AC servo motor output (W)		750	400	400	200
Maximum speed (XYZ:m/sec) (R:°/sec)		8.4		2.3	1.7
Standard cycle time: with 2kg payload ² (sec)		0.42			
R axis allowable moment inertia ³ (kgm ²)		1			
User wiring (sq x pcs)		0.2 x 20			
User tubing (Outer diameter)		Ø6 x 3			
Movement limit setting		1.Soft limit 2.Mechanical stopper (X, Y, Z axis)			
Robot cable length (m)		Standard: 3.5 Option: 5, 10			
Weight (kg) (Excluding robot cable)		Z axis 200mm: 50, Z axis 400mm: 52			

- *1 This is the value at a constant ambient temperature. (X,Y axes)
- *2 When moving 25mm in vertical direction and 300mm in horizontal direction reciprocally.
- *3 There are limits to the setting of the acceleration coefficient.


Controller

Controller	Power consumption (VA)	Operating method
YRC	2500	Programming / I/O point trace / Remote command / Operation using RS-232C communication

Ordering information

Description	Model
SCARA Reach: 700mm, Vertical Stroke: 200mm, Max. payload: 20kg.	R6YXG700200YRC
SCARA Reach: 700mm, Vertical Stroke: 400mm, Max. payload: 20kg.	R6YXG700400YRC

Dimensions



R6YXG800 XG SERIES

Specifications

		X axis	Y axis	Z axis	R axis
Reach (mm)		800			
Maximum payload (kg)		20			
Repeatability ^{*1} (XYZ:mm) (R:°)		+/-0.02		+/-0.01	+/-0.004
Axis specifications	Arm length (mm)	400	400	200	400
	Rotation range (°)	+/-130	+/-150	----	+/-360
Deceleration mechanism	Speed reducer	Harmonic drive	Harmonic drive	Ball screw	Harmonic drive
	Transmission method	Motor to speed reducer	Direct-coupled		
		Speed reducer to output	Direct-coupled		
AC servo motor output (W)		750	400	400	200
Maximum speed (XYZ:m/sec) (R:°/sec)		9.2		2.3	1.7
Standard cycle time: with 2kg payload ^{*2} (sec)		0.48			
R axis allowable moment inertia ^{*3} (kgm ²)		1			
User wiring (sq x pcs)		0.2 x 20			
User tubing (Outer diameter)		Ø6 x 3			
Movement limit setting		1.Soft limit 2.Mechanical stopper (X, Y, Z axis)			
Robot cable length (m)		Standard: 3.5 Option: 5, 10			
Weight (kg) (Excluding robot cable)		Z axis 200mm: 52, Z axis 400mm: 54			

- *1 This is the value at a constant ambient temperature. (X,Y axes)
- *2 When moving 25mm in vertical direction and 300mm in horizontal direction reciprocally.
- *3 There are limits to the setting of the acceleration coefficient.


Controller

Controller	Power consumption (VA)	Operating method
YRC	2500	Programming / I/O point trace / Remote command / Operation using RS-232C communication

Ordering information

Description	Model
SCARA Reach: 800mm, Vertical Stroke: 200mm, Max. payload: 20kg.	R6YXG800200YRC
SCARA Reach: 800mm, Vertical Stroke: 400mm, Max. payload: 20kg.	R6YXG800400YRC

Dimensions



SCARA Robots XG series

Ordering information

	Series	Reach (mm)	Z-axis stroke (mm)	Payload (kg)	Robot item code	RGU	Robot cable length (m)	Cable item code	Detachable robot cable
R6Y	XG	120	50	1	R6YXG12050YRC	N.A.	2.0	R6YACCX002T1	N.A.
							3.5	R6YACCX003T1	N.A.
							5.0	R6YACCX005T1	N.A.
							10.0	R6YACCX010T1	N.A.
	XG	150	50	1	R6YXG15050YRC	N.A.	2.0	R6YACCX002T1	N.A.
							3.5	R6YACCX003T1	N.A.
							5.0	R6YACCX005T1	N.A.
							10.0	R6YACCX010T1	N.A.
	XG	180	50	1	R6YXG18050YRC	N.A.	2.0	R6YACCX002T1	N.A.
							3.5	R6YACCX003T1	N.A.
							5.0	R6YACCX005T1	N.A.
							10.0	R6YACCX010T1	N.A.
	XG	220	100	1	R6YXG220100YRC	N.A.	3.5	R6YACCX003T2	N.A.
							5.0	R6YACCX005T2	N.A.
							10.0	R6YACCX010T2	N.A.
	XG	500	200	10	R6YXG500200YRC	RGU3	3.5	R6YACCX003XGX	●
							5.0	R6YACCX005XGX	●
							10.0	R6YACCX010XGX	●
			300	10	R6YXG500300YRC	RGU3	3.5	R6YACCX003XGX	●
							5.0	R6YACCX005XGX	●
							10.0	R6YACCX010XGX	●
	XG	600	200	10	R6YXG600200YRC	RGU3	3.5	R6YACCX003XGX	●
							5.0	R6YACCX005XGX	●
							10.0	R6YACCX010XGX	●
			300	10	R6YXG600300YRC	RGU3	3.5	R6YACCX003XGX	●
							5.0	R6YACCX005XGX	●
							10.0	R6YACCX010XGX	●
	XGH	600	200	20	R6YXGH600200YRC	RGU3	3.5	R6YACCX003XGX	●
							5.0	R6YACCX005XGX	●
							10.0	R6YACCX010XGX	●
			400	20	R6YXGH600400YRC	RGU3	3.5	R6YACCX003XGX	●
							5.0	R6YACCX005XGX	●
							10.0	R6YACCX010XGX	●
	XG	700	200	20	R6YXG700200YRC	RGU3	3.5	R6YACCX003XGX	●
							5.0	R6YACCX005XGX	●
							10.0	R6YACCX010XGX	●
			400	20	R6YXG700400YRC	RGU3	3.5	R6YACCX003XGX	●
							5.0	R6YACCX005XGX	●
							10.0	R6YACCX010XGX	●
	XG	800	200	20	R6YXG800200YRC	RGU3	3.5	R6YACCX003XGX	●
							5.0	R6YACCX005XGX	●
							10.0	R6YACCX010XGX	●
400			20	R6YXG800400YRC	RGU3	3.5	R6YACCX003XGX	●	
						5.0	R6YACCX005XGX	●	
						10.0	R6YACCX010XGX	●	
R6Y	XG	900	200	20	R6YXG900200YRC	RGU3	3.5	R6YACCX003XGX	●
							5.0	R6YACCX005XGX	●
							10.0	R6YACCX010XGX	●
			400	20	R6YXG900400YRC	RGU3	3.5	R6YACCX003XGX	●
							5.0	R6YACCX005XGX	●
							10.0	R6YACCX010XGX	●
	XG	1000	200	20	R6YXG1000200YRC	RGU3	3.5	R6YACCX003XGX	●
							5.0	R6YACCX005XGX	●
							10.0	R6YACCX010XGX	●
			400	20	R6YXG1000400YRC	RGU3	3.5	R6YACCX003XGX	●
							5.0	R6YACCX005XGX	●
							10.0	R6YACCX010XGX	●

ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.

To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.